



STAMFORD LEROY-SOMER

Output Ratings		
Speed,Frequency/Volt	Prime Power	Standby Power
1500rpm, 50 Hz / 400V	320KWe/400KVA	360KWe/450KVA

Genset Specifications	
Engine Make & Model	Cummins QSG12-G4
Origin	China
Alternator Type	S4L1D-F41/TAL0473A
Control Panel	Deep Sea - 7310 MKII
Circuit BreakerType	3 Pole MCCB
Water Cooling System	
Electronic Governor	

Fuel System (prime)	50%	75%	100%
1500rpm, 50 Hz (L/hr)	41	60	82

International Standards

Engine confirm to ISO 9001: 2000, ISO 14001, ISO 10054, ISO 3046, BS 5514, DIN 6271.

Alternator confirm to ISO 9001, ISO 14001, BS EN 60034, BS 5000, VDE 0530, NEMA MG1-32, IEC34 CSA C22.2-100, AS 1359, BS 6861 1, B En 61000-6-2:2001



RATING GUIDELINES

PRIME POWER rating corresponds to ISO Standard Power for continuous operation. It is applicable for supplying electrical power at variable load for an unlimited number of hours instead of commercially purchased power. A10 % overload capability for govering purpose is available for this rating.

MAXIMUM STANDBY POWER rating corresponds to ISO Standard Fuel Stop Power. It is applicable for supplying standby electrical power at variable load in areas with well established electrical networks in the event of normal utility power failure. No overload capability is available for this rating. I hp = 1 kW x 1.36

Engine Technical Data	
No. of Cylinders / Alignment	6/ In Line
Cycle	4 - Stroke
Aspiration	Turbocharged
Injection	Direct
Bore, mm	132
Stroke, mm	140
Displacement,I	11.8
Compression Ratio	17.0:1
Starting	24V Electric
Alternators, Amps	24V

Alternator Technical Data	
No. of Bearings	Single Bearing
Insulation System	Class H
Excitation	Self Excited
Voltage Regulator	AS440/R150
Protection	IP23
Temperature Rise,°C	Prime 125/40 Standby 163/27
Regulation	±1.0% - ±0.8%
No. of Phases	3
No. of Poles	4



STAMFORD LEROY-SOMER

Performances	I500rpm
Alternator Efficiency	93.4%
Engine Power Prime Power, KWm(hp) Standby Power, KWm(hp)	371(498) 409(549)
Alternator Prime Power, KWe	320

Lubrication System	I500rpm
Oil Consumption (I/hr)	-
Oil Sump Capacity,I	34.1
Oil System Capacity Include Filters,I	34.1

Cooling System	I500rpm	
Heat Radiation from Engine and Alternator, Power KW	31	
Heat Rejection to Coolant and Lube Oil at Standby Power, KW	214	
Radiator Cooling Air Flow, m³/s (cfm)	8.4(17798)	1
Coolant Capacity, I	38	

Intake & Exhaust System	I500rpm
Air Flow Combustion at Standby Power, m³/min(cfm)	25.4(898)
Heat Rejection Exhaust at Standby Power, KW	286
Exhaust Gas Temperature at Standby °C	524
Max Allowable Back Pressure in Exhaust Line, Kpa	10.2
Exhaust Gas Flow at Standby Power, m³/min(cfm)	61.7(2179)

Accessories	
Standard Silencer	Anti-Vibration Pads
Stainless Steel Flexible	Genuine Coolant 'Ready Mix'

Genuine Oil

Control Panel Readings

- AC volts, AC currents, DC volts, frequency, rpm, hour counter, power factor.
- Low oil pressure, high water temparature, boost pressure and temperature, KW, KWh, KVA, KVAR
- Oil pressure, low oil level, high oil temperature
- DC alternator failure, over speed, over crank (Fail to start), over under voltage, over under current, any sensor failure
- Low coolant level Configurable inputs&outputs
- Upgradable for GSM network connection, Signal SMS messages.

Optional Equipment

- Engine
- -Coolant heater
- -Oversize batteries
- -Extra fuel pre-filter water separator
- -Battery Disconnector Switch
- -Electrical Governor
- Alternator
- -Excitation Boost System (EBS)
- -Upgrade to 3 phase sensing AVR
- -Qadrature droop kit
- -Anti-condensation heater
- -Air inlet filters
- General
- -Upgrade to modular controller for paralleling
- -Upgrade to 4 pole circuit breaker
- -Battery charger
- -Automatic transfer switch
- -Fuel level switch High / Low for alarm and control
- -Fuel transfer pump Automatic / Manual
- -Residential grade silencer
- -Weather protective and acoustic enclosure.

Spare Parts Kit (Optional)	Genuine - Cummins
Oil filter Fuel filter	(1) (2)
Air filter Fan belt set	(I) (I)
Coolant filter	(l)
Consultation of the	

General Information

Documentation

Engine instruction book-English Alternator manual- English Wiring diagram

Warranty

One year with unlimited hours against all defects in material or workmanship, subject to the terms and conditions of the Manufacturer's warranty

